# **Sprinkler System Spare Parts Kit**

August 28, 2007

# For Removing Paint from PVC so that Pipes Can Be Spliced

- 1. Acetone (primer can also be used to remove paint).
- 2. Steel wool.
- 3. Rubber gloves.

## For Repairing/Splicing PVC Pipe

- 1. Several feet of 3" PVC.
- 2. Several feet of 2" PVC.
- 3. 3" and 2" caps for sealing a section of irrigation pipe in case patches/repairs are not possible.
- 4. Tape measure.
- 5. Pencil/marker.
- Crosscut saw or hacksaw.
- 7. 2 or more 3" couplers [Important cautionary note: Irrigation pipe couplers are different from what is sold at hardware stores and home centers. Get irrigation pipe couplers.]
- 8. 2 or more 2" couplers [See above cautionary note.]
- 9. Glue. [Important cautionary note: Glue in previously opened cans may have a limited shelf life and may solidify. PVC glue should be in a new, unopened can.]
- 10. Primer.

### For Repairing Goodyear Rubber Hose

- 1. 1" couplers.
- 2. ¾" couplers.
- 3. Hose Clamps (2 per coupler).
- 4. Screw driver for fastening hose clamps.

### Other

- 1. Sprinkler head(s)
- 2. Wrenches for removing and replacing sprinkler heads. *Recommendation:* One Crescent wrench and one channel lock pliers.
- 3. Duct tape.
- 4. Pump cap.